

FALC

MONDIAL

**ELEVATORE IDRAULICO - ELEVATEUR HYDRAULIQUE
- HYDRAULIC FORKLIFT - HYDRAULIK-STAPLER -
ELEVADOR HIDRÁULICO**



**Elevatori idraulici con 2 sfili, per trattori.
Portata kg 1500**



**Elévateurs hydrauliques double télescopique, pour tracteurs.
Capacité de charge Kg 1500**



**Double telescopic hydraulic forklifts, for tractors.
Load capacity Kg 1500**




**2-stufiger Hydraulik-Stapler, für Traktoren.
Leistung Kg 1500**



**Elevadores hidráulicos telescópicos dobles, para tractores.
Capacidad de carga kg 1500**



MONDIAL		PORTATA PORTE LOAD CAPACITY HEBEGEWICHT CAPACIDAD DE CARGA	ALTEZZA DI SOLLEVAMENTO HAUTEUR D' ELEVATION LIFTING HEIGHT HEBEHÖHE ALTURA DE ELEVACIÓN	BRANDEGGIO AVANTI INDIETRO POINTAGE EN AVANT EN ARRIERE FORWARD/BACKWARD FORKS NACH-VORNE-KIPPEN MOVIMIENTO HACIA ADELANTE Y ATRÁS	TRASLATORE LATERALE TRANSLATEUR LATERAL SIDESHIFTER SEITENVERSTELLUNG DESPLAZADOR LATERAL
	kg	kg	mm		mm
3200	440	1500	3200	12° - 17°	100 + 100



A	3200 mm
B	2323 mm
C	300 mm

